

STOCK COMPACT TRUCK

STOCK COMPACTS TO FOLLOW STOCK FULL SIZE TRUCK RULES EXCEPT:

NO REAR END BIGGER THAN 8LUG, CAN NOT BE BRACED BUT CAN HAVE PINION BRAKE AND SLIDER.

BUMPER HEIGHT MUST BE BELOW 21IN

NO FULL-SIZE BRONCOS, BLAZERS. ALL VEHICLES MUST BE UNDER A HALF TON.

FRONT DRIVESHAFT MUST BE REMOVED ON 4X4 TRUCKS.

No full engine cradles- only lower cradles allowed that can attach to the front of the engine. All other motor mounts must be stock in compact class.

Carburetor and header protector can only mount to the engine.

V8 SWAPS WILL BE ALLOWED.

HOMEMADE BUMPERS WILL BE ALLOWED, BUT MUST BE MADE FROM A SINGLE 4X4X1/4IN HOLLOW PIECE OF SQUARE TUBING OR PIPE, NO POINT.

FULLSIZE CAR AND TRUCK BUMPERS WILL BE ALLOWED.

YOU CAN RUN ANY WHEEL AND TIRE COMBO YOU WANT.

FOR ANY QUESTIONS CONTACT:

SCHUYLER TOTTEN OR ALAN GARRETT AT 719-980-2925